

Code: APTI-N0911-4P-I3

## NVR **APTI-N0911-4P-I3** 9 CHANNELS, 4 PoE

Net: **91.25 EUR** Gross: **91.25 EUR**

The APTI-N0911-4P-I3 digital recorder is a professional device applicable in surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

**Attention!** The built-in PoE switch only supports APTI cameras.



### SPECIFICATION

|                                     |                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                                                                                                           |
| Supported resolutions:              | max. 8 Mpx - 3840 x 2160 px, 4K UHD                                                                                                                                                                                                                                                              |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA                                                                                                                                                                                                                                                                       |
| Audio support:                      | <ul style="list-style-type: none"><li>• 9 Channels - Audio from cameras</li><li>• Bi-directional audio streaming support</li></ul>                                                                                                                                                               |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                                                                                                                                                                                      |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                                                                                                      |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264                                                                                                                                                                                                                                                                  |
| Bitrate:                            | 80 Mbps                                                                                                                                                                                                                                                                                          |
| Supported hard drives:              | 1 x 8 TB SATA                                                                                                                                                                                                                                                                                    |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                                                                                                                                                                                       |
| External storage devices backup:    | Records backup at (.avi) format to USB (pendrive)                                                                                                                                                                                                                                                |
| Searching and playback the records: | Records searching: timeline or file list. Playback: forward, fast<br>Playback max. 4 cameras in the same time @ 1080p                                                                                                                                                                            |
| Network interface:                  | 1 x RJ-45 10/100 Base-TX                                                                                                                                                                                                                                                                         |
| Network functions:                  | Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters                                                                                                                                                                  |
| Network protocols:                  | IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE                                                                                                                                                                                                         |
| ONVIF:                              | ✓                                                                                                                                                                                                                                                                                                |
| Default IP address:                 | 192.168.1.88                                                                                                                                                                                                                                                                                     |
| Default admin user / password:      | admin / 12345                                                                                                                                                                                                                                                                                    |
| Mobile phones support:              | Access by a cloud (P2P)<br><ul style="list-style-type: none"><li>• Android: Free application <a href="#">BitVision</a>, Android: Free application <a href="#">iVMS320</a></li><li>• Android: Free application <a href="#">BitVision</a>, iOS: Free application <a href="#">iVMS320</a></li></ul> |
| Web browser access ports:           | 80, 5000, 554                                                                                                                                                                                                                                                                                    |
| PC client access ports:             | 80, 5000, 554                                                                                                                                                                                                                                                                                    |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                                                                                                                                                                           |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USB:                             | 2 pcs USB 2.0                                                                                                                                                             |
| Serial ports:                    | —                                                                                                                                                                         |
| Alarm inputs / outputs:          | 4 / 1                                                                                                                                                                     |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                                     |
| Motion Detection:                | Split the screen into zones : 22 x 18 motion zones                                                                                                                        |
| Intelligent Image Analysis:      | ✓                                                                                                                                                                         |
| Main features:                   | <ul style="list-style-type: none"> <li>• Support for intelligent image analysis, available in cameras from the APTI-AI series</li> <li>• D-ZOOM - Digital Zoom</li> </ul> |
| Mouse support:                   | ✓                                                                                                                                                                         |
| IR remote controller in the set: | —                                                                                                                                                                         |
| Switch PoE:                      | 4-port PoE Switch built-in : 15 W / Channel - PoE (802.3af)                                                                                                               |
| Maximum total switch load:       | 50 W                                                                                                                                                                      |
| Power supply:                    | 48 V DC / 1.36 A (power adapter included)                                                                                                                                 |
| Power consumption:               | ≤ 10 W (without HDD)                                                                                                                                                      |
| Operation temp:                  | -10 °C ... 50 °C                                                                                                                                                          |
| Weight:                          | 0.96 kg                                                                                                                                                                   |
| Dimensions:                      | 260 x 237 x 45 mm                                                                                                                                                         |
| Supported languages:             | Polish, English, French, Spanish, German, Portuguese, Russian, Ukrainian, Italian                                                                                         |
| Manufacturer / Brand:            | APTI                                                                                                                                                                      |
| Guarantee:                       | 2 years                                                                                                                                                                   |

## PRESENTATION

Front panel:



Rear panel:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|