Code: BCS-NVR32025ME-II

NVR **BCS-NVR32025ME-II** 32 CHANNELS

Net: 296.61 EUR Gross: 296.61 EUR



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	32 @ 3840 x 2160 px, 32 @ 3072 x 2048 px, 32 @ 2560 x 1920 px, 32 @ 2688 x 1520 px, 32 @ 2048 x 1536 px, 32 @ 1920 x 1080 px, 32 @ 1280 x 720 px
Video outputs:	1 pcs HDMI - 4K UHD 1 pcs VGA
Audio support:	32 Channels
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.264 / MJPEG
Maximal total frame rate:	800 fps @ 3840 x 2160 px , 800 fps @ 3072 x 2048 px , 800 fps @ 2560 x 1920 px , 800 fps @ 2688 x 1520 px , 800 fps @ 2048 x 1536 px , 800 fps @ 1920 x 1080 px , 800 fps @ 1280 x 720 px
Supported hard drives:	2 x 6 TB SATA III
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, IP Filter, PPPoE, FTP, IP Search, Lechange, ONVIF 2.4
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow "Frame by Frame" playback function All channels synchronous playback, Smart Search function
Bitrate:	200 Mbps (total)
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 128 on-line users

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp:	-10 °C ... 50 °C
ONVIF:	✔
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address:	192.168.1.108
Default admin user / password:	admin / admin
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs:	4 pcs / 2 pcs
PTZ control:	IP Speed Dome Cameras
Motion Detection:	22 x 18 motion zones 6 sensitivity levels
Intelligent Image Analysis:	✔
Mouse support:	✔
IR remote controller in the set:	–
Power supply:	12 V DC / 4 A (power adapter included)
Weight:	1.6 kg
Dimensions:	375 x 285 x 55 mm
Supported languages:	English, Polish
Country of origin:	China
Manufacturer / Brand:	BCS
Guarantee:	**3 years**

PRESENTATION

Front panel:



Rear panel:



In the kit:



OUR OPINIONS

- Audio transmission via network.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg