

Code: APTI-N6428AI-I3

NVR **APTI-N6428AI-I3** 64 CHANNELS

Net: **402.53 EUR** Gross: **402.53 EUR**

The APTI-N6428AI-I3 digital recorder is a professional device applicable in surveillance systems. The H.265+ video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 12 Mpx - 4000 x 3000 px
Video outputs:	• 1 pcs HDMI 4K • 1 pcs HDMI • 1 pcs VGA
Audio support:	• 64 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Bitrate:	640 Mbps
Supported hard drives:	8 x 10 TB SATA + 1 x eSATA
Recording modes:	Manual, Sensor, Motion detection, Schedule
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p
Network interface:	2 x RJ-45 10/100/1000 Base-TX
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters
Network protocols:	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE
ONVIF:	✓
Default IP address:	192.168.1.88
Default admin user / password:	admin / 12345
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Mobile phones support:	Access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • Android: Free application BitVision , iOS: Free application iVMS320
USB:	• 2 pcs USB 2.0 • 1 pcs USB 3.0
Serial ports:	RS-485
Alarm inputs / outputs:	16 / 4
PTZ control:	• IP Speed Dome Cameras • RS-485 control
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Intelligent Image Analysis:	✓
Main features:	• Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom
Mouse support:	✓
IR remote controller in the set:	—
Switch PoE:	—
Power supply:	100 ... 240 V AC, 50 / 60 Hz
Power consumption:	≤ 20 W (without HDD)
Operation temp:	-10 °C ... 50 °C
Weight:	7.46 kg
Dimensions:	440 x 430 x 100 mm
Supported languages:	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Ukrainian, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Front panel:



Rear panel:




See how to mount a hard disk drive and configure the recorder:

:

In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------