

Code: BNC-W/4879

COMPRESSION PLUG **BNC-W/4879** RG6 NS100 Triset113

Net: 0.72 EUR Gross: 0.72 EUR



BNC plug crimped on coaxial cable.  
The kind of material used eliminates any corrosion. High precision ensures low loss and insertion force, as well as nice look. It can be compressed with ease, providing stable high performance connectivity for a long time.  
The connector is produced under strict technological discipline. The plug is tight in the socket, there is no risk of losing the contact, which takes place in the case of cheap connectors. The inner conductor of the cable inserted into the inlet is centered and stopped.

SPECIFICATION

|                                   |                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector type:                   | BNC Plug                                                                                                                                                                                                                                                                                                                                              |
| Attachment of connector elements: | Compression mounting                                                                                                                                                                                                                                                                                                                                  |
| Application:                      | Coaxial cable                                                                                                                                                                                                                                                                                                                                         |
| Wire mounting:                    | Pressing                                                                                                                                                                                                                                                                                                                                              |
| Dielectric diameter:              | max. 4.8 mm                                                                                                                                                                                                                                                                                                                                           |
| Cable diameter:                   | max. 7.9 mm                                                                                                                                                                                                                                                                                                                                           |
| Shield fastening:                 | Compression mounting                                                                                                                                                                                                                                                                                                                                  |
| Watertightness:                   | ✓                                                                                                                                                                                                                                                                                                                                                     |
| Example of application:           | <ul style="list-style-type: none"><li>• RG6,</li><li>• NS100-TRISHIELD</li><li>• Triset113</li></ul>                                                                                                                                                                                                                                                  |
| Main features:                    | <ul style="list-style-type: none"><li>• Properly compressed connection is highly resistant to break</li><li>• Watertightness of connector with cable connection</li><li>• Very easy and quick assembly</li><li>• Corrosion resistance</li><li>• Very low loss in the whole operating band</li><li>• To crimp use the crimping tool HT-5082R</li></ul> |
| Weight:                           | 0.013 kg                                                                                                                                                                                                                                                                                                                                              |
| Dimensions:                       | Ø 14.5 mm x 39 mm                                                                                                                                                                                                                                                                                                                                     |
| Guarantee:                        | 2 years                                                                                                                                                                                                                                                                                                                                               |

PRESENTATION

Connector view from cable assembly side:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Top view:



Terminating of BNC compression connectors using a compression tool:  
:

#### PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60