

Code: KN-CA51

SIDE MAGNETIC CONTACT **KN-CA51**

Net: **4.34 EUR** Gross: **4.34 EUR**

The magnetic contacts can be used wherever required for controlling the status of doors, windows and/or other movable elements, e.g. for protection or monitoring of access to particular sites, spaces, facilities, in automatic control systems, etc.

The contact is designed for surface mounting.




SPECIFICATION

Detection:	Opening the door or window
Maximum reed switched voltage:	20 V
Maximal switched current:	20 mA
Make distance:	18 mm
Break distance:	20 mm
Main features:	• Metal housing • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable : 25 cm • Leads out the cables : On the short edge
Color:	Silver
Weight:	0.04 kg
Dimensions:	31.2 x 14.4 x 7.6 mm
Guarantee:	2 years

PRESENTATION

Dimensions:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60