

Code: JA-110B

ACOUSTIC GLASS BREAK DETECTOR **JA-110B** JABLOTRON

Price visible after login



Sensor signals an alarm on registering a low-frequency tone (impact sound), followed by a high-frequency tone (sound of broken glass). The sensor starts to analyze a high-frequency channel after receiving the low-frequency sound wave, caused by the impact.

SPECIFICATION

Support:	JABLOTRON 100
Detection:	Glass break detector
Range:	max. 9 m
Environment class:	II
Sensitivity adjustment:	—
Alarm signaling:	LED indicator, Signal to control panel (Control panel BUS)
Power supply:	Control panel BUS, 12 V
Main features:	• detection of breaking plate, laminated or tempered glass • advanced dual-path microprocessor signal analysis
Color:	White
Operation temp:	-10 °C ... 40 °C
Weight:	0.045 kg
Dimensions:	40 x 100 x 22 mm
Manufacturer / Brand:	JABLOTRON
Guarantee:	2 years

PRESENTATION

View after remove the cover:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------