

Code: AGD-200

WIRELESS GLASS BREAK DETECTOR **AGD-200** ABAX/ABAX2 SATEL

Net: **61.66 EUR** Gross: **61.66 EUR**

Sensor signals an alarm on registering a low-frequency tone (impact sound), followed by a high-frequency tone (sound of broken glass). The sensor starts to analyze a high-frequency channel after receiving the low-frequency sound wave, caused by the impact.

The AGD-200 supports the other devices compatible with wireless ABAX/ABAX2 system.



SPECIFICATION

Detection:	detection of breaking plate, laminated or tempered glass
Support:	ABAX/ABAX2
Alarm signaling:	Signal to control panel
Frequency band:	868 MHz ... 868.6 MHz
Radio communication range (at open area):	• ~ 500 m @ ABAX, • ~ 2000 m @ ABAX2
Battery:	CR123A 3 V - 3.0 V (included)
Backup time:	~ 2 years
Main features:	• advanced dual-path microprocessor signal analysis • Remote configuration • Tamper protections
Operation temp:	-10 °C ... 55 °C
Color:	White
Weight:	0.02 kg
Dimensions:	20 x 102 x 23 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION

Internal view of the housing:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

