


Code: PK1-12-ZD

NORMALLY OPEN RELAY MODULE **PK1-12-ZD** DELTA

Net: 6.65 EUR Gross: 6.65 EUR



It can be used to increase maximal load of controller transistor output line and for galvanic isolation between output line and load point.

SPECIFICATION

Number of relay outputs:	1
Power supply:	10 ... 16 V DC
Current consumption:	35 mA 12 V DC
Relay maximal load:	10 A (max), 30 V DC / 50 V AC (max)
Output:	NO
Application:	
Main features:	• DIN, TS-35 rail mounting, • LED indication, • Protections : Overvoltage, Reverse polarity connection
Operation temp:	-10 °C ... 40 °C
Weight:	0.03 kg
Dimensions:	73 x 12 x 41 mm
Manufacturer / Brand:	DELTA
Guarantee:	3 years



PRESENTATION

Top view:




Connectors:


DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Mounting side view:



Schematic diagram:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------