

Code: PD-6/R-SPD-3L

POWER DISTRIBUTION UNIT **PD-6/R-SPD-3L**

Net: **21.47 EUR** Gross: **21.47 EUR**

Power distribution unit allows to connect up to 6 devices simultaneously, with a maximum load of 3680 W. The device is mounted to RACK 19" cabinet.



SPECIFICATION

Rated voltage:	230 V AC / 50 Hz
Total maximal current:	16 A
Maximal total load:	3680 W
Number of outlets:	6 x CEE 7/5
Assembly:	In RACK 19" cabinets
Length of the power cable:	1,8 m cable with power connector CEE 7/7
Nominal voltage of surge suppressor:	250 V / 50 Hz
Housing type:	1 U RACK 19"
Switch:	two-way, with light indication
Main features:	• Signaling a lack of grounding • Overvoltage protection • AC input voltage presence indication
Weight:	0.78 kg
Dimensions:	483 x 45 x 54 mm
Guarantee:	2 years

PRESENTATION

Power outlets:



LED diodes:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Switch:



CEE 7/7 plug:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------