

Code: LZ-24/R19

POWER SUPPLY DISTRIBUTOR LZ-24/R19

Net: 129.00 PLN Gross: 158.67 PLN

The LZ-24/R19 is a passive device that enables power ordered distribution from one or several higher power units.
If necessary the terminals can be connected in parallel.



SPECIFICATION

Number of power outputs:	24 (4 x 6 outputs)
Number of power inputs:	4 (one per each 6-outputs terminal)
Maximal power voltage:	24 V DC (typical 12V)
Maximal power supply current:	5 A (for single terminal)
Max. output current for single output:	1 A
Protection type:	24 x 1 A - 5/20mm delayed fuse
Power connectors type:	Input : Cable terminals Output : Cable terminals
Operation temp:	-50 °C ... 55 °C
Permissible relative humidity:	< 95 %
Housing type:	1 U Rack 19"
Weight:	0.35 kg
Dimensions:	484 x 44 x 33 mm
Manufacturer / Brand:	DELTA
Guarantee:	3 years

PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Rear view:



Top view:



Schematic diagram of distributor application with two different voltages option:

