

Code: POE-48/2E

POWER ADAPTER VIA TWISTED-PAIR CABLE **POE-48/2E**

Net: **14.77 EUR** Gross: **14.77 EUR**

The POE-48/2E is designed to powering devices using PoE technology. This technology allows to run the system with only one UTP/FTP cable which transmits data and provides supplying voltage.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



SPECIFICATION

Standards:	IEEE 802.3at
Input voltage:	100 V ... 240 V AC
Output voltage:	48 V DC
Number of inputs:	1
Connector:	2 x RJ-45 socket
LED indicators:	Power connection
Output power:	24 W
Protections:	—
Housing:	Plastic
Operation temp. / Relative humidity:	0 °C ... 40 °C / 5 % 90 %
Weight:	0.224 kg
Dimensions:	85 x 43 x 30 mm
Guarantee:	2 years

PRESENTATION

Adapter connectors:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

