

Code: HPSB-7012C

BUFFERED SWITCHING POWER SUPPLY ADAPTER **HPSB-7012C**

Net: **71.50 EUR** Gross: **71.50 EUR**

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment.
Please pay attention for proper cooling conditions of the power adaptor during work!



SPECIFICATION


Adapter type:	Switching
Input voltage:	176 V ... 264 V AC
Output voltage:	9.5 V ... 13.8 V
Max. output current (total):	6 A
Battery charging current:	1 A
Power:	100 W
Number of outputs:	1
Protections:	• Short-circuit • Overload • Overvoltage • Tamper • Reverse polarity connection • Discharge
Adapter operation control:	• AC input voltage presence indication AC • DC output voltage presence indication DC
Place for battery:	12V/17Ah
Max. battery dimensions:	250 x 185 x 80 mm
Weight:	2.3 kg
Dimensions:	295 x 285 x 90 mm
Manufacturer / Brand:	PULSAR
Guarantee:	2 years

PRESENTATION

Internal view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




Front view:



Mounting side view:



Dimensions:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------