

Code: DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK

IP CAMERA **DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK** PANORAMIC
ColorVu - 7.4 Mpx 2 x 4 mm Hikvision
Net: **721.92 EUR** Gross: **721.92 EUR**

The IP camera is equipped with 2 high quality image sensors and 2 lenses with 4 mm focal length. Thanks to its unique design, the camera has a 180° viewing angle.

Attention! The camera of the ColorVu series does not have a black and white mode. Thanks to fit the camera in a very sensitive sensor and the LED illuminator emitting visible light in white, the device allows to obtain a clear, colorful image in all lighting conditions. PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



SPECIFICATION

Standard:	TCP/IP
Sensor:	2 x 1/1.8 " Progressive Scan CMOS
Matrix size:	2 x 3.7 Mpx - 8 Mpx (total)
Scanning system:	Progressive
Resolution:	5120 x 1440 - 7.4 Mpx
Lens:	2 x 4 mm
View angle:	180 ° (horizontal) 44 ° (vertical)
White light LED illuminator range:	40 m
RS-485 interface:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	1 / 1
Audio:	• Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support • Digital Noise Reduction
Main stream frame rate:	20 fps @ 7.4 Mpx
Network interface:	10/100 Base-T (RJ-45)
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect

Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
WEB Server:	Built-in
Max. number of on-line users:	6
ONVIF:	✓
Main features:	• WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Active deterrence function - Light and sound alarm • White light (LED) illuminator built-in : 4 LEDs • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Configurable: brightness, contrast, saturation • Smart motion detection (with recognizing people and vehicles) • Intelligent Image Analysis - crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing
Power supply:	• 12 V DC / 790 mA, • PoE (802.3af)
Power consumption:	• ≤ 9.5 W @ 12 V DC • ≤ 10.5 W @ PoE
Housing:	Compact, Metal
Color:	Black
Vandal-proof:	—
"Index of Protection":	IP67
Operation temp:	-30 °C ... 60 °C
Weight:	1.45 kg
Dimensions:	119 x 105 x 305 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
SAP Code:	311323807
Manufacturer / Brand:	Hikvision
Guarantee:	3 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Side view:



Bottom view:






Memory card slot and "Reset" button:



Mounting side view:



Connectors:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in LED illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60