

Code: DL2-150-24-U

SWITCHING ADAPTER **DL2-150-24-U**

Net: **43.26 EUR** Gross: **43.26 EUR**

Switching adapter installed on the TS35/7.5 or 15 DIN rail, resistant to high operation temperatures (up to 70°C).



SPECIFICATION


Adapter type:	Switching
Power voltage:	• 85 ... 264 V AC • 120 ... 370 V DC
Output voltage:	24 V DC
Output voltage adjustment:	21.6 ... 29 V DC
Maximal load:	• 5.31 A @ 100 ... 120 V AC, • 6.25 A @ 200 ... 240 V AC
Output power:	• 127 W @ 100 ... 120 V AC, • 150 W @ 200 ... 240 V AC
Number of outputs:	2 pcs
Efficiency:	91.5 %
Housing type:	DIN
Protections:	• Short-circuit • Overload • Overvoltage • Temperature
Operation temp. / Relative humidity:	-30 °C ... 70 °C / 10 ... 95 %
Weight:	0.33 kg
Dimensions:	105 x 90 x 58 mm
Guarantee:	3 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Adapter connectors:



Top view:



Rear panel (DIN rail installation):



