

Code: APTI-304V2-28WP

IP CAMERA **APTI-304V2-28WP** - 3 Mpx 2.8 mm

Net: **345.70 DKK** Gross: **345.70 DKK**

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 3 MPx.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.9 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	• 95 ° (manufacturer data) • 100 ° (our tests result)
Range of IR illumination:	20 m
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	—
Main stream frame rate:	max. 25 fps @ 3 Mpx
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP
WEB Server:	Built-in - port 80
Max. number of on-line users:	10
ONVIF:	2.4

Main features:	• Intelligent Image Analysis : intrusion • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • Flicker Control - The technology eliminates the tiring eyes flickering image effect • ROI - improve the quality of selected parts of image • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Motion Detection • Privacy zones • Day/night mode • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Power supply:	• PoE (802.3af), • 12 V DC / 340 mA
Power consumption:	≤ 4.1 W
Housing:	Dome - Metal
Vandal-proof:	—
Color:	White
"Index of Protection":	—
Operation temp:	-20 °C ... 60 °C
Weight:	0.3 kg
Dimensions:	Ø 94 x 74 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Camera is out from clamping ring:



Mounting side view:



In the kit:



OUR TESTS


Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------