

Code: BCS-L-EIP25FSR5-AI2

IP CAMERA **BCS-L-EIP25FSR5-AI2** - 5 Mpx 2.8 mm BCS Line

Net: **295.49 EUR** Gross: **295.49 EUR**

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 MPx. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Thanks to the "DarkView Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	• 111 ° (manufacturer data) • 105 ° (our tests result)
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG / AI Coding
Range of IR illumination:	50 m
Alarm inputs / outputs:	1 / 1
Main stream frame rate:	25 fps - 5 Mpx
Network interface:	10/100 Base-T (RJ-45)
Audio:	• Microphone built-in • Audio transmission via network • Audio detection • Compliance with the AAC standard

WEB Server:	Built-in
Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording)
Max. number of on-line users:	20
ONVIF:	22.06
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	• Main stream : rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 • Sub stream : rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1
RS-485 interface:	—
Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Motion Detection - max. 4 configurable zones • Privacy zones - max. 4 • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), fast moving, loitering detection, detection of people gathering, detection of entry into the area / exit from the area, illegal parking, classification of people and vehicles, abandoned/missing object, scene changing, advanced face capture features, counting people / vehicles, metadata support, heat map • Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity
Power supply:	• PoE (802.3af), • 12 V DC / 700 mA
Power consumption:	max. 8.3 W
Housing:	Dome, Metal
Color:	White
"Index of Protection":	IP67
Vandal-proof:	—
Operation temp:	-40 °C ... 60 °C
Supported languages:	Polish, English
Weight:	0.52 kg
Dimensions:	Ø 106 x 94 mm
Manufacturer / Brand:	BCS Line
Guarantee:	3 years



PRESENTATION

Camera is out from clamping ring:




Memory card slot:



Camera mounting side view:





In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------