

Code: BCS-L-EIP14FR3

## IP CAMERA **BCS-L-EIP14FR3** - 4 Mpx 2.8 mm BCS Line

Net: **1 710.97 SEK** Gross: **1 710.97 SEK**

IP camera with efficient H.264+ / H.265+ image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



### SPECIFICATION

|                               |                                                                                                                                                 |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                     | IP                                                                                                                                              |
| Resolution:                   | 2688 x 1520 - 4 Mpx ,<br>2560 x 1440 - 3.7 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 960 - 1.3 Mpx<br>1280 x 720 - 720p |
| Sensor:                       | 1/3 " Progressive Scan CMOS                                                                                                                     |
| Lens:                         | 2.8 mm @ F2.0                                                                                                                                   |
| View angle:                   | 93 °                                                                                                                                            |
| Range of IR illumination:     | 30 m                                                                                                                                            |
| Memory card slot:             | —                                                                                                                                               |
| Image compression method:     | H.265+ / H.265 / H.264+ / H.264 / MJPEG                                                                                                         |
| Alarm inputs / outputs:       | —                                                                                                                                               |
| Audio:                        | —                                                                                                                                               |
| Main stream frame rate:       | • 20 fps @ 4 Mpx<br>• 25 fps @ 3.7 Mpx                                                                                                          |
| Interface:                    | 10/100 Base-T (RJ-45)                                                                                                                           |
| WEB Server:                   | Built-in                                                                                                                                        |
| Max. number of on-line users: | 20                                                                                                                                              |
| ONVIF:                        | ✓                                                                                                                                               |
| Intelligent image analysis:   | —                                                                                                                                               |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:                 | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• AGC - Automatic Gain Control</li> <li>• AES - Auto Electronic Shutter</li> <li>• Image rotation and mirror</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• AWB - Auto White Balance</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 4</li> <li>• D-ZOOM - Digital Zoom : 16 x</li> </ul> |
| Mobile phones support:         | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BCS Manager</a><br>• iOS (iPhone): Free application <a href="#">BCS Manager</a>                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Default IP address:            | 192.168.1.108                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Web browser access ports:      | 80, 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| PC client access ports:        | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Mobile client access ports:    | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| RTSP URL:                      | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Power supply:                  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 420 mA</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Power consumption:             | max. 5 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Housing:                       | Dome - Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Color:                         | White                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| "Index of Protection":         | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Mechanical protection class:   | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Operation temp:                | -40 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Weight:                        | 0.31 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Dimensions:                    | Ø 93 x 80 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Supported languages:           | Polish, English                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Manufacturer / Brand:          | BCS Line                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## PRESENTATION


Camera is out from clamping ring:



Camera mounting side view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60