

Code: CD-75A4

CARBON MONOXIDE (CO) DETECTOR **CD-75A4** EURA

Net: **19.82 EUR** Gross: **19.82 EUR**

The CD-75A4 microprocessor-based digital gas detectors are characterized by reliability and low current consumption. A digital temperature compensation feature allows to operate within a wide temperature range. Gas concentration above the threshold level triggers visual and audible alarm signals. Device should be mounted at a height of about 0.7 ... 1.5 m above the floor.



SPECIFICATION

Detection:	Carbon Monoxide (CO)
Alarm signaling:	• Buzzer • Blinking LED
Gas concentration to trigger alarm:	300 ppm for max. 3 mins
Battery power supply:	3 x battery LR6 (AA) (included) Current consumption < 90 µA - Standby
Main features:	• Low battery level alarm • Alarm siren 85 dB/m • Test mode • Detection max. 25 m² • LCD display • Thermometer built-in • Displays the concentration of the CO gas in the air in range of 25 ... 550 ppm
Operation temp:	0 °C ... 40 °C
Weight:	0.226 kg
Dimensions:	120 x 90 x 40 mm
Manufacturer / Brand:	EURA
Guarantee:	2 years

PRESENTATION

Front panel:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Internal view:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------