

Code: HY-GB40A

LPG (PROPANE) GAS DETECTOR **HY-GB40A** WISUALARM / DAHUA

Net: **32.74 EUR** Gross: **32.74 EUR**

The HY-GB40A is a device designed for continuous monitoring of LPG (propane) concentration in the air. The MCU-based, digital gas detectors are distinguished by high sensitivity and stable performance, quick response time as well as a low level of false alarms.

Gas concentration above the threshold level triggers visual and audible alarm signals. The control outputs of the detector enable the connection of an external fan and a gas cut-off valve. The detectors are intended to be used as part of a security system.



SPECIFICATION

Detection:	LPG (propane) gas
Alarm signaling:	• Buzzer 70 dB / 1 m • Blinking LED • Signal to control panel
Gas concentration to trigger alarm:	10% Lower Explosive Limit (LEL)
Prealarm feature:	—
Autodiagnostics:	✓
Main features:	• Relay output : NO (fan control by switching voltage), • Output to control the gas cut-off valve • Measurement response time ≤ 30 s • Alarm mute function • TEST/SILENCE button • LED diodes indicating the device operation status
Power supply:	12 V DC / 1 A (power adapter included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.09 kg
Dimensions:	87 x 87 x 26 mm
Manufacturer / Brand:	WISUALARM / DAHUA
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front panel:




Connectors:



Mounting side view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------