

Code: JA-81MB

WIRELESS MAGNETIC CONTACT **JA-81MB** JABLOTRON

Price visible after login

The JA-81MB wireless detector (magnetic contact) is used to protection the windows and doors. Additionally the device is equipped with IN1, IN2, TMP inputs, which enable connecting any wire detector. The detector is also designed to detect the mishandling of security roller blinds. The device communicates with alarm control panel wirelessly via OASiS protocol.



SPECIFICATION


Support:	JABLOTRON 80
Detection:	• Opening the door or window, • Mishandling of security roller blinds, • The IN1, IN2, TMP inputs, which enable connecting any wire detector
Alarm signaling:	Signal to control panel
Frequency range:	868 MHz OASiS protocol
Radio communication range (at open area):	max. 300 m
Alarm inputs:	IN2, TMP = NC IN1 = NC or parameterized 1k
Battery:	LS(T)14500 type 3.6 V (not included)
Backup time:	~ 3 years (20 activations a day)
Environment class:	Grade 2
Operation temp:	-10 °C ... 40 °C
Color:	Brown
Weight:	0.04 kg
Dimensions:	• Transmitter : 110 x 31 x 25 mm • Magnet A : 56 x 16 x 15 mm • Magnet B : 10 x 4 mm
Manufacturer / Brand:	JABLOTRON
Guarantee:	2 years

PRESENTATION

Inner view, type A magnet and transmitter:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------