

Code: DS-2CC12D9T-E

HD-TVI, PAL CAMERA **DS-2CC12D9T-E** - 1080p PoC.af Hikvision

Net: **197.30 EUR** Gross: **197.30 EUR**

Megapixel camera with Progressive Scan CMOS sensor and HD-TVI (High Definition Transport Video Interface).

The HD-TVI interface allows to transmission of analog video signal via coaxial cable at resolutions up to 1080p. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

The ability to power the camera via a coaxial cable according to the innovative PoC (Power over Coaxial) standard allows to eliminate the need for additional wiring to the unit.



SPECIFICATION

Standard:	HD-TVI, PAL
Sensor:	Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p, HD-TVI , 960 x 576 - 960H, PAL
Video output:	• 1 Vpp / 75 Ω - HD-TVI • 1 Vpp / 75 Ω - CVBS, PAL
Lens:	—
Auto Iris socket:	DC
S/N ratio:	> 62 dB
Min. illumination:	0.01 Lux @ F1.2
IR illuminator support:	—
Audio:	—
Alarm inputs / outputs:	1 / 1
RS-485 interface:	✓
OSD menu:	✓

Main features:	• 3D-DNR - Digital Noise Reduction • WDR - 120 dB - Wide Dynamic Range • The ability to power the camera via a coaxial cable according to the innovative PoC (Power over Coaxial) standard allows to eliminate the need for additional wiring to the unit • LOW-LIGHT Scene (Sense-UP - Slow Shutter) - Increase the sensor sensitivity • BLC/HLC - Back Light / High Light Compensation • Mirror - Mirror image • Motion Detection - max. 4 configurable zones • Privacy zones - max. 8 • Sharpness - sharper image outlines • Auto White Balance
Power supply:	12 V DC / 580 mA , PoC.af
Power consumption:	≤ 7 W
Housing:	BOX, Plastic
Color:	White
Operation temp:	-30 °C ... 60 °C
Weight:	0.39 kg
Dimensions:	147 x 69 x 58 mm
Supported languages:	English, Arabic, Chinese Traditional, Chinese Simplified, French, Hebrew, Spanish, Dutch, German, Portuguese, Polish, Russian, Turkish, Italian
SAP Code:	300505348
Manufacturer / Brand:	Hikvision
Guarantee:	3 years

PRESENTATION

Front view:



Side view:



Bottom view:



Rear view:





In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at direct strong light opposite to camera:



Camera image at night conditions, at different illumination values show below:

10 LUX:



1 LUX:



0.1 LUX:



0.01 LUX:



0.001 LUX:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------