

Code: STT-1

AHD, HD-CVI, HD-TVI, PAL VIDEO TESTER **STT-1**

Net: **227.23 EUR** Gross: **227.23 EUR**



SPECIFICATION

Video standard:	AHD-H, AHD-M, HD-CVI, HD-TVI, PAL, NTSC
Display:	7 " TFT LCD 800 x 480
Video input:	• 1 pcs HD-TVI, AHD-H, AHD-M, HD-CVI - BNC socket • 1 pcs HDMI • 1 pcs VGA • 1 pcs Video composite (BNC socket)
Video output:	• 1 pcs Video composite (Cinch socket) • 1 pcs HD-TVI, HD-CVI, AHD-H, AHD-M - Cinch socket
Audio inputs:	—
Video signal level meter:	—
Video signal generator:	• Test signal generator • Eight color-bars generating in multi-tv-system modes
Serial ports:	—
LAN (twisted-pair) or telephone cables testing:	—
RS-485, RS-232 lines test:	—
Identification the wire in the group of wires:	—
Audio test:	—
Digital multimeter:	—
Optical power measurement:	—
TDR reflectometer:	—
Operation as power source:	• 12 V DC / 2 A
Power supply:	• Li-Ion battery 12.6 V, 2600 mAh • 12 V DC / 1 A (power adapter included)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Estimated battery operation time:	max. 17 hours
Operation:	OSD
Main features:	• Control the PTZ HD-TVI cameras via coaxial cable • Access to the OSD menu of the HD-TVI cameras via coaxial cable • Test signal generator • DC 12V / 2A power source
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	30 % ... 90 %
Weight:	0.655 kg
Dimensions:	205 x 155 x 40 mm
Supported languages:	English, French, Spanish, German, Russian, Italian
Guarantee:	2 years

PRESENTATION

Front panel:



Top view:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------