

Code: MCT84M

## PROXIMITY READER **MCT84M** ROGER

Net: **107.55 EUR** Gross: **107.55 EUR**



Indoor reader of proximity cards and key-fobs designed to work in the RACS 5 access control and building automation system. 13.56 MHz S50 standard.

### SPECIFICATION

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Support:                       | RACS 5 (Roger)                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Cards support:                 | 13.56 MHz S50                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Reading distance of prox-keys: | max. 5 cm                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Keyboard built-in:             | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Autonomous operation:          | —                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Doorbell button:               | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Tamper output:                 | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Communication:                 | RS-485                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Main features:                 | <ul style="list-style-type: none"><li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li><li>• Keypad backlight buttons</li><li>• LED indication</li><li>• Beep signal</li><li>• Reads card numbers: CSN, SSN, MSN</li><li>• Support for normal and long card reading method</li><li>• Configuration through RS-485 (RogerVDM)</li><li>• Firmware upgrade via RS-485 (Roger VDM) port</li></ul> |
| Power supply:                  | 10 ... 15 V DC                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Average current consumption:   | ~ 50 mA                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Operation temp:                | -10 °C ... 50 °C                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Permissible relative humidity: | 10 ... 95 % (non-condensing)                                                                                                                                                                                                                                                                                                                                                                                                             |
| "Index of Protection":         | IP41                                                                                                                                                                                                                                                                                                                                                                                                                                     |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                       |                  |
|-----------------------|------------------|
| Weight:               | 0.1 kg           |
| Dimensions:           | 130 x 45 x 22 mm |
| Manufacturer / Brand: | ROGER            |
| Guarantee:            | <b>3 years</b>   |

## PRESENTATION

Front panel:



Rear view:





Internal view, after remove the cover:



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|