

Code: B-2S-BR

## CYLINDRICAL MAGNETIC CONTACT **B-2S-BR** SATEL

Net: **2.91 EUR** Gross: **2.91 EUR**

The magnetic contacts can be used wherever required for controlling the status of doors, windows and/or other movable elements, e.g. for protection or monitoring of access to particular sites, spaces, facilities, in automatic control systems, etc.

The magnetic contact element containing the magnet should be mounted on the movable part, while the reed switch - on the stationary part of protected doors, windows, etc. The sunk magnetic contact is designed for face mounting in such materials as wood or plastic.

The contact is to be pressed in.



### SPECIFICATION

|                                |                            |
|--------------------------------|----------------------------|
| Detection:                     | Opening the door or window |
| Maximum reed switched voltage: | 100 V                      |
| Maximal switched current:      | 500 mA                     |
| Make distance:                 | 25 mm                      |
| Break distance:                | 27 mm                      |
| Length of the cable:           | 44 cm                      |
| Main features:                 | Small dimensions           |
| Color:                         | Brown                      |
| Dimensions:                    | 27 x 6.5 mm                |
| Weight:                        | 0.01 kg                    |
| Manufacturer / Brand:          | SATEL                      |
| Guarantee:                     | 2 years                    |

### PRESENTATION



### PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

