

Code: VMT-072

MONITOR 2xVIDEO **VMT-072** 7 "

CCTV monitor in plastic housing.

The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.

The device is designed to continuous work in closed spaces.



Screen size:	7 "
Native resolution:	800 x 480 px
Aspect ratios:	16 : 10
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	500 : 1
Brightness:	250 cd/m ²
Viewable angles:	120 ° horizontal 110 ° vertical
Response time:	25 ms
Speakers built-in:	—
Signal connectors:	<ul style="list-style-type: none"> • Composite Video (BNC) sockets: 2x in • VGA (D-Sub 15-pin)
Housing type:	Plastic
Monitor mounting standard:	Monitor bracket with adjusted tilt in range 90 °
Power supply:	12 V DC / 1 A (power adapter included)



DATA SHEET

Power consumption:	max. 10 W (operation) < 1 W (Standby mode)
Monitor control:	OSD - by monitor control keys
Main features:	Auto Picture Adjustment
Operation temp:	-10 °C ... 50 °C
Weight:	0.58 kg
Dimensions:	178 x 119 x 75 mm (with stand) 178 x 119 x 25 mm (without stand)
Supported languages:	English, Chinese Simplified, French, Spanish, German, Polish, Portuguese, Russian, Italian
Guarantee:	2 years

