

Code: DH-HAC-HFW1220RP-028

AHD, HD-CVI, HD-TVI, PAL CAMERA **DH-HAC-HFW1220RP-028** - 1080p 2.8 mm DAHUA

Attention! The camera default setting is HD-CVI standard. To change the camera standard you need use the PFM820 controller, available separately.

Megapixel camera with 1/2.9" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

Camera is according to IP67 Index of Protection norm.



Standard:	HD-CVI, HD-TVI, AHD, PAL
Sensor:	1/2.9 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
IR illuminator support:	ICR - Movable InfraRed filter
Resolution:	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL
Lens:	2.8 mm
View angle:	106 °
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Video output:	HD-CVI / HD-TVI / AHD / PAL - 1 Vpp / 75 Ω
S/N ratio:	> 65 dB
OSD menu:	✓, OSD menu available via recorder

Main features:	<ul style="list-style-type: none">• D-WDR - Wide Dynamic Range• 2D-DNR - Digital Noise Reduction• BLC/HLC - Back Light / High Light Compensation• ICR - Movable InfraRed filter• Sharpness - sharper image outlines• AGC - Automatic Gain Control• Privacy zones• Mirror - Mirror image• Auto White Balance• To change the standard, in which the camera is operating, the PFM820 controller is required
Power supply:	12 V DC / 230 mA
Power consumption:	≤ 2.8 W
Housing:	Compact, Plastic
Color:	White
"Index of Protection":	IP67
Operation temp:	-40 °C ... 60 °C
Weight:	0.21 kg
Dimensions:	154 x 70 x 70 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years