

Code: APTI-H32V3-2812W

## AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA **APTI-H32V3-2812W** - 3.0 Mpx, 1080p 2.8 ... 12 mm

Megapixel camera with 1/3" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 3.0 Mpx (HD-TVI) / 1080p (AHD, HD-CVI) resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

Setting the camera in PAL mode allows to obtain an image in 960H resolution. The appropriate signal format selection is done by tilting and holding the joystick for 5 s without entering to the OSD menu. Changing the signal to the NTSC in the camera causes loss of image in connected AHD recorder.



Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/3 " APTINA CMOS
Digital Image Processor:	Nextchip NVP2470H
Matrix size:	3.0 Mpx
Resolution:	2048 x 1536 - 3.0 Mpx @ HD-TVI , 1920 x 1080 - 1080p @ AHD-H, HD-CVI, HD-TVI , 960 x 576 - 960H @ PAL
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 ... 12 mm, 3 Mpx
View angle:	<ul style="list-style-type: none"> <li>• 89 ° ... 27 ° (manufacturer data)</li> <li>• 74 ° ... 29 ° (our tests result)</li> </ul>
S/N ratio:	> 50 dB
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch

Main features:	<ul style="list-style-type: none"><li>• ICR - Movable InfraRed filter</li><li>• D-WDR - Wide Dynamic Range</li><li>• DNR - Digital Noise Reduction</li><li>• AGC - Automatic Gain Control</li><li>• Sharpness - sharper image outlines</li><li>• Auto White Balance</li></ul>
OSD menu:	✓
Power supply:	12 V DC / 400 mA
Power consumption:	≤ 4.8 W
Housing:	Dome - Metal
Color:	White
Vandal-proof:	✓
"Index of Protection":	IP66
Operation temp:	-10 °C ... 50 °C
Weight:	0.59 kg
Dimensions:	Ø 120 x 83 mm
Supported languages:	English, Chinese, French, Spanish, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years