

Code: LE-337222

FLUSH-MOUNTING DISTRIBUTION CABINET 48-MODULAR **LE-337222** XL³ S 160 LEGRAND

2-row 48-modular flush-mounting distribution electric cabinet.
NOTE: Doors and terminal blocks must be ordered separately.



Method of mounting:	Flush-mounted
Number of mounted modules:	24 x 2 rows
Spacing between TH 35 rails:	150 mm
Transparent door:	(not included)
Main features:	• Easily adjustable depth of the TH 35 chassis • Large capacity • Monobloc housing • Flexibility in the selection of terminal blocks • Possibility of connecting the housings vertically • Max. current : 160 A • Short-circuit current : 17 kA • Equipped with faceplates at full height
Equipment:	Faceplates : 1 x 2R
Material:	Steel
Color:	White
"Index of Protection":	• IP30 (without door) • IP40 (with door)

IK rating:	• IK04 (without door) • IK07 (with door)
Compliance with standards:	IEC/EN 61439-1, IEC/EN 61439-3, IEC 60695-2-1
Operation temp:	-5 °C ... 40 °C
Weight:	10.76 kg
Dimensions:	665 x 510 x 135 mm , 595 x 440 x 135 mm - flush-mounting box
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years