

## DATA SHEET

Code: XB-KINDER

## ELECTRONIC BABY MONITOR XB-KINDER Xblitz

The XB-KINDER baby monitor is a wireless device operating in 2.4 GHz band. The maximal transmission range is 260 m in the open area, and approx.  $50\ m$  in rooms.

The device enables one-way video transmission and bidirectional audio transmission. In addition, the module intended for mounting in a baby's room has 8 built-in lullaby melodies. The playing of the melody is triggered by pressing a dedicated button on the module with the monitor.

The device also allows to monitor the air temperature in the baby's room.





| Display:                          | 3.2 " TFT LCD   |
|-----------------------------------|---|
| Video resolution:                 | 320 x 240 px  |
| Audio:                            | Bi-directional audio streaming support  |
| Memory:                           | -   |
| Range of IR illumination:         | 5 m   |
| Power supply:                     | Monitor - 5V / 1000mA power adapter (in the set) or from built-in backup battery     Camera - 5V / 1000mA power adapter (included)  |
| Estimated battery operation time: | ~ 8 hours   |
| Wireless transmission range:      | • 260 m (in open area) • 50 m (inside buildings)  |
| Frequency range:                  | 2.4 GHz 2.4835 GHz  |
| Application:                      | Device is designed for indoor use only  |
| Main features:                    | Sounds (melodies) - 8 pcs     VOX standby mode - the screen of the device on the parent side remains blanked until noise is detected in the room with the camera or the button is pressed                     |
| Main leatures:                    | Built-in thermometer in camera module     Image and sound from the camera module are transmitted continuously, while communication from the monitor side takes place in a push-to-talk system                 |
| Housing:                          | Built-in thermometer in camera module     Image and sound from the camera module are transmitted continuously, while  |
|                                   | Built-in thermometer in camera module     Image and sound from the camera module are transmitted continuously, while communication from the monitor side takes place in a push-to-talk system                 |
| Housing:                          | Built-in thermometer in camera module     Image and sound from the camera module are transmitted continuously, while communication from the monitor side takes place in a push-to-talk system  Plastic        |
| Housing: Color:                   | Built-in thermometer in camera module     Image and sound from the camera module are transmitted continuously, while communication from the monitor side takes place in a push-to-talk system  Plastic  White |





## DATA SHEET

| Manufacturer / Brand: | Xblitz  |
|-----------------------|---|
| Supported languages:  | English, French, Spanish, German, Polish, Portuguese, Russian, Turkish, Italian |
| Guarantee:            | 2 years   |