

Code: DS-KH6310

INDOOR PANEL IP **DS-KH6310** Hikvision

The DS-KH6310 panel has been designed to create a simple and effective system of local communication.

The device cooperates with video doorphones, and other panels working in Hikvision IP standard. It can be also used as simple alarm control panel, or notification module by the support 8 alarm inputs.

The device is fully configurable via the **iVMS4200** software. In addition, the device has the ability to work with the **Hik-Connect** application on mobile devices.



Compatibility:	Interphone installation - Hikvision
Shield:	7 " capacitive touch screen
Resolution:	800 x 480
Internal memory:	256 MB (built-in)
Main features:	<ul style="list-style-type: none"> • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save images after the bell button pressing, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices
Controlling:	Large, readable buttons + capacitive touch screen
Default administrator password:	123456
Default password for securing the zone:	123456
Alarm inputs:	8
Power supply:	<ul style="list-style-type: none"> • 12 V DC / 830 mA, • 24 V PoE



DATA SHEET

Color:	White
Operation temp:	-10 °C ... 55 °C
Weight:	0.37 kg
Dimensions:	197 x 134 x 27 mm
Supported languages:	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305300148
Guarantee:	3 years