

## DATA SHEET

## Code: HDMI+USB-EX-100/RX EXTENDER RECEIVER **HDMI+USB-EX-100/RX** SIGNAL

Device allows to send High Definition signal to the TV-Set receiver equipped with HDMI connector via UTP Cat. 5e, 6 cable. Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse.

To TV set you need connect only one UTP cable, what makes installation easy and improve aesthetic quality of installation.

The signal bit-rate at the transmitter output is approximately 20 Mb/s, which results in a slight visible compression effect. The recommended minimum distance of watching from the screen is 2m ... 3m.

Attention! The device operates from the monitor side.



| Device type:                   | Receiver  |
|--------------------------------|---|
| Supported HDMI resolutions:    | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p  |
| Maximal transmission range:    | 100 m UTP cat. 5e, 6  |
| Protocols:                     | HDbitT  |
| Main features:                 | <ul> <li>Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse</li> <li>The devices do not require direct connection, they also operate via the LAN network</li> <li>Audio transmission via network</li> </ul> |
| Power supply:                  | 5 V DC / 1 A (power adapter included)   |
| Operation temp:                | -10 °C 60 °C  |
| Permissible relative humidity: | 20 % 90 % (non-condensing)  |
| Weight:                        | 0.168 kg  |
| Dimensions:                    | 110 x 89 x 26 mm  |
| Manufacturer / Brand:          | SIGNAL  |
| Guarantee:                     | 2 years   |



HDMI+USB-EX-100/RX