

Code: DHI-NVD0405DH-4K

IP DECODER **DHI-NVD0405DH-4K** - 12 Mpx, 4K

The DHI-NVD0405DH-4K decoder allows to manage displaying images up to 4 monitors with the HDMI connector. The device is fully configurable over the network, and the managed screens can display images from the IP cameras and directly from the HDMI device inputs.



Supported resolutions:	4 Channels @ 4000 x 3000 px - 12 Mpx , 4 Channels @ 3840 x 2160 px - 4K , 16 Channels @ 1920 x 1080 - 1080p , 36 Channels @ 1280 x 720 - 720p , 64 Channels @ 704 x 576 - D1
Number of supported screens:	4 pcs
Video inputs:	1 x HDMI 4K
Video outputs:	• 4 x HDMI 4K, • 4 x VGA, • 4 x BNC
audio input:	• 1 x HDMI • 1 x BNC - External microphone input
Audio outputs:	• HDMI • 4 x BNC • 1 x BNC - Headphones output
Network interface:	1 x RJ45 10/100/1000 Base-T
Default IP address:	192.168.1.108
Default admin user / password:	admin / -
Serial ports:	• 1 pcs RS-232 @ RJ45 • 1 pcs RS-232 @ D-Sub • 1 pcs RS-485 • 2 pcs USB
Alarm inputs / outputs:	4 / 4
Power supply:	12 V DC / 5 A (power adapter included)
Power consumption:	≤ 20 W
Operation temp:	-10 °C ... 55 °C
Weight:	3.4 kg
Dimensions:	440 x 300 x 42 mm - RACK 19", 1U
Supported languages:	English



DATA SHEET

Manufacturer / Brand:	DAHUA
Guarantee:	3 years