

Code: MS-ACTHD50-5MP

AHD, HD-CVI, HD-TVI, PAL MONITOR **MS-ACTHD50-5MP** 5 "

Multi-functional tester of AHD, HD-CVI, HD-TVI cameras, analog cameras, Speed Dome (PTZ) cameras has implemented many additional functions, necessary during initialization of the CCTV installation system.

Attention! The tester has no protection against excessive battery discharge. Excessive discharge of batteries may lead to battery damage, tester damage or image disturbances.



Standard:	AHD - 5 Mpx, HD-CVI - 4 Mpx, HD-TVI - 5 Mpx, PAL, NTSC
Screen size:	5 "
Native resolution:	800 x 480 px
Image adjustment:	✓
Sleep function:	—
OSD menu:	✓
Video input:	• 1 pcs - AHD / HD-CVI / HD-TVI / CVBS - PAL / NTSC, BNC socket • 1 pcs VGA (D-Sub 15-pin) - 1024 x 768, 1280 x 720, 1280 x 1024 • 1 pcs HDMI - 1024 x 768, 1280 x 720, 1280 x 1024
Video output:	1 pcs CVBS - PAL, BNC socket
Audio input:	1 pcs Jack 3.5 mm socket
Audio output:	—
RS-485 interface:	Pelco-D / Pelco-P The motozoom lens control works only via RS-485 255 addresses Baudrate : 1200 / 2400 / 4800 / 9600 / 14400
Operation as power source:	12 V DC / 0.4 A
Battery power supply:	Li-Ion battery

Power supply:	• 2 x 18650 battery 3.7 V • 5 V DC / 1 A - micro USB (power adapter included)
Estimated battery operation time:	max. 11 hours
Main features:	LAN (twisted-pair) cables testing
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	30 % ... 90 %
Weight:	0.38 kg
Dimensions:	173 x 114 x 36 mm
Supported languages:	English, Chinese Traditional, Chinese Simplified
Guarantee:	2 years