

DATA SHEET

Code: M-GSM GSM COMMUNICATION MODULE **M-GSM** VIDOS



The M-GSM module allows to increase the functionality of selected 2wire models of VIDOS internal panels by the possibility of sending an alarm SMS message and redirecting the call to a maximum of 3 userdefined phone numbers. Call forwarding allows for a telephone conversation with the person at the door station and remote opening of the wicket or gate.

The defined telephone numbers are selected in the order set by the user, but the failure to answer one of the numbers results in the next one being called.

The device can be used both in 1-storey and multi-family installations. The module requires the installation of an active SIM card from the national operator.

Compatibility:	VIDOS DUO - M1021, M1022
Antenna connector:	SMA
Assembly:	DIN, TS-35 rail mounting
Power supply:	24 V DC
Power consumption:	1.56 W (Standby mode) 13 W (operation)
Main features:	 Support up to 3 subscriber numbers, The ability to transfer calls from the door station to a landline or mobile phone, Remote release of electric strike, Possibility to mount on a wall, or on the DIN TS-35 rail
Weight:	0.18 kg
Dimensions:	90 x 72 x 61 mm
Manufacturer / Brand:	VIDOS
Guarantee:	2 years



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60