

Code: APTI-H24C9-2812G

AHD, HD-CVI, HD-TVI, PAL CAMERA **APTI-H24C9-2812G** - 1080p 2.8 ... 12 mm

Megapixel camera with 1/2.9" Sony CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

Setting the camera in PAL mode allows to obtain an image in 960H resolution. The appropriate signal format selection is done by tilting and holding the joystick for 5 s without entering to the OSD menu. Changing the signal to the NTSC in the camera causes loss of image in connected AHD recorder.



Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/2.9 " Sony CMOS IMX323
Digital Image Processor:	HTC1088
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p, AHD, HD-CVI, HD-TVI , 960 x 576 - 960H, PAL
Range of IR illumination:	60 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 ... 12 mm, 2 Mpx
View angle:	• 83 ° ... 23 ° (manufacturer data) • 95 ° ... 35 ° (our tests result)
S/N ratio:	> 50 dB
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch

Main features:	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • White Balance - ATW/Manual • Privacy zones - max. 4 • Motion Detection - max. 4 zones • BLC - configurable Back Light Compensation • Sharpness - sharper image outlines
OSD menu:	✓
"Index of Protection":	IP66
Power supply:	12 V DC / 540 mA
Power consumption:	≤ 6.5 W
Housing:	Compact - Metal
Color:	Graphite
Operation temp:	-20 °C ... 50 °C
Weight:	0.77 kg
Dimensions:	222 x 82 x 84 mm
Supported languages:	English
Manufacturer / Brand:	APTI
Guarantee:	2 years