

Code: NVR608R-64-4KS2

## NVR **NVR608R-64-4KS2** 64 CHANNELS +eSATA DAHUA



|                                     |                                                                                                                                          |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                   |
| Supported resolutions:              | max. 12 Mpx - 4000 x 3000 px                                                                                                             |
| Video outputs:                      | 2 pcs HDMI<br>1 pcs VGA                                                                                                                  |
| Audio support:                      | 64 Channels - Audio from cameras                                                                                                         |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                              |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                              |
| Image compression method:           | H.265 / H.264 / MJPEG                                                                                                                    |
| USB:                                | 2 pcs USB 2.0<br>2 pcs USB 3.0                                                                                                           |
| Supported hard drives:              | 8 x 8 TB SATA + 1 x eSATA<br>Operation modes : SINGLE, Raid 0/1/5/6/10                                                                   |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                               |
| Network protocols:                  | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search<br>ONVIF 2.4 |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive) - 2 x Port USB 3.0                                                                        |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>"Frame by Frame" playback function        |
| Bitrate:                            | max. 384 Mbps (total)                                                                                                                    |
| Power consumption:                  | ≤ 20 W (without HDD)                                                                                                                     |
| Network functions:                  | Full support via network, Remote records copying, Web Server built-in<br>max. 128 on-line users                                          |
| ONVIF:                              | 2.4                                                                                                                                      |

|                                  |                                                                                                                                                                                                                                                                  |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile phones support:           | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a><br><br>See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Default IP address:              | 192.168.1.108                                                                                                                                                                                                                                                    |
| Default admin user / password:   | admin / admin                                                                                                                                                                                                                                                    |
| Web browser access ports:        | 80, 37777                                                                                                                                                                                                                                                        |
| PC client access ports:          | 37777                                                                                                                                                                                                                                                            |
| Mobile client access ports:      | 37777                                                                                                                                                                                                                                                            |
| RTSP URL:                        | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                  |
| Alarm inputs / outputs:          | 16 pcs / 8 pcs                                                                                                                                                                                                                                                   |
| PTZ control:                     | RS-485 - Many protocols<br>IP Speed Dome Cameras                                                                                                                                                                                                                 |
| Motion Detection:                | 22 x 18 motion zones                                                                                                                                                                                                                                             |
| Intelligent image analysis:      | ✓                                                                                                                                                                                                                                                                |
| Mouse support:                   | ✓                                                                                                                                                                                                                                                                |
| IR remote controller in the set: | —                                                                                                                                                                                                                                                                |
| Main features:                   | • Ability to work drives in a RAID array can significantly improve system reliability<br>• Redundant power supply - The recorder has been equipped with two separate power supply adapters                                                                       |
| Power supply:                    | 100 V ... 240 V AC                                                                                                                                                                                                                                               |
| Weight:                          | 8.74 kg (without HDD)                                                                                                                                                                                                                                            |
| Dimensions:                      | 444 x 457 x 95 mm                                                                                                                                                                                                                                                |
| Supported languages:             | Polish, English                                                                                                                                                                                                                                                  |
| Country of origin:               | China                                                                                                                                                                                                                                                            |
| Manufacturer / Brand:            | DAHUA                                                                                                                                                                                                                                                            |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                                                                   |