

Code: NVR1B04HC/E

## NVR **NVR1B04HC/E** 4 CHANNELS EZ-IP DAHUA

The devices from the EZ-IP series are ideal for small and medium applications, such as security for homes, apartments and small shops. The NVR1B04HC/E is characterized by exceptional efficiency and it is easy to use.



|                                     |                                                                                                                                                                                                            |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                     |
| Supported resolutions:              | max. 6.3 Mpx - 3072 x 2048 px                                                                                                                                                                              |
| Video outputs:                      | 1 pcs HDMI<br>1 pcs VGA                                                                                                                                                                                    |
| Audio support:                      | 4 Channels - Audio from cameras                                                                                                                                                                            |
| Audio inputs:                       | —                                                                                                                                                                                                          |
| Audio outputs:                      | —                                                                                                                                                                                                          |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264                                                                                                                                                                            |
| Supported hard drives:              | 1 x 4 TB SATA                                                                                                                                                                                              |
| Recording modes:                    | Manual, Motion Detection, Schedule                                                                                                                                                                         |
| Network protocols:                  | HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, IP Search, P2P                                                                                                                       |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                                             |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function |
| Network functions:                  | Full support via network, Remote records copying, Web Server built-in<br>max. 128 on-line users                                                                                                            |
| Bitrate:                            | max. 40 Mbps                                                                                                                                                                                               |
| Default admin user / password:      | admin / -<br>The administrator password should be set at the first start                                                                                                                                   |
| Default IP address:                 | 192.168.1.108                                                                                                                                                                                              |



# DATA SHEET

|                                  |                                                                                                                                                                                                                                                                  |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RTSP URL:                        | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                  |
| Web browser access ports:        | 80, 37777                                                                                                                                                                                                                                                        |
| PC client access ports:          | 37777                                                                                                                                                                                                                                                            |
| Mobile client access ports:      | 37777                                                                                                                                                                                                                                                            |
| Mobile phones support:           | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a><br><br>See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Alarm inputs / outputs:          | —                                                                                                                                                                                                                                                                |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                                                                                                                            |
| Motion Detection:                | 22 x 18 motion zones                                                                                                                                                                                                                                             |
| USB:                             | 2 x USB 2.0                                                                                                                                                                                                                                                      |
| Mouse support:                   | ✓                                                                                                                                                                                                                                                                |
| IR remote controller in the set: | —                                                                                                                                                                                                                                                                |
| Power supply:                    | 12 V DC / 1.5 A                                                                                                                                                                                                                                                  |
| Weight:                          | 0.51 kg                                                                                                                                                                                                                                                          |
| Dimensions:                      | 201 x 192 x 41 mm                                                                                                                                                                                                                                                |
| Supported languages:             | Polish, English                                                                                                                                                                                                                                                  |
| Country of origin:               | China                                                                                                                                                                                                                                                            |
| Manufacturer / Brand:            | DAHUA                                                                                                                                                                                                                                                            |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                                                                   |