

Code: CD-65A4

## CARBON MONOXIDE (CO) DETECTOR **CD-65A4** EURA

The CD-65A4 microprocessor-based digital gas detectors are characterized by reliability and low current consumption. A digital temperature compensation feature allows to operate within a wide temperature range.

Gas concentration above the threshold level triggers visual and audible alarm signals. Device should be mounted at a height of about 0.7 ... 1.5 m above the floor.



Detection:	Carbon Monoxide (CO)
Alarm signaling:	<ul style="list-style-type: none"> <li>• Buzzer</li> <li>• Blinking LED</li> </ul>
Gas concentration to trigger alarm:	300 ppm for max. 3 mins
Battery power supply:	3 x battery LR6 (AA) (included) Current consumption < 90 µA - Standby
Main features:	<ul style="list-style-type: none"> <li>• Low battery level alarm</li> <li>• Alarm siren 85 dB/m</li> <li>• Test mode</li> <li>• Detection max. 25 m<sup>2</sup></li> <li>• LCD display</li> <li>• Thermometer built-in</li> <li>• Displays the concentration of the CO gas in the air in range of 25 ... 550 ppm</li> </ul>
Operation temp:	0 °C ... 40 °C
Weight:	0.226 kg
Dimensions:	120 x 90 x 40 mm
Manufacturer / Brand:	EURA
Guarantee:	2 years