

Code: DS-2AE7232TI-A(C)

AHD, HD-CVI, HD-TVI, CVBS SPEED DOME CAMERA OUTDOOR **DS-2AE7232TI-A(C)** - 1080p 4.8 ... 153 mm Hikvision

Megapixel camera with 1/2.8" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals. Camera is according to IP66 Index of Protection norm.



Standard:	AHD, HD-CVI, HD-TVI, CVBS
Sensor:	1/2.8 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 960 x 576 - 960H
Range of IR illumination:	150 m
Lens:	4.8 ... 153 mm
View angle:	• 54 ° ... 2 ° (manufacturer data) • 54 ° ... 2.5 ° (our tests result)
Optical zoom:	x 32
Digital zoom:	x 16
Rotation speed depending on ZOOM level:	✓
Horizontal rotation range:	360 ° continuous

Vertical rotation range:	-15 ° ... 90 °
Rotation speed (manual control):	0.1 °/s ... 160 °/s (horizontal) , 0.1 °/s ... 120 °/s (vertical)
Preset rotation speed:	160 °/s (horizontal) 120 °/s (vertical)
PTZ control:	Via interface RS-485 The ability to control via coaxial cable from recorder HIKVISION
Protocols:	Pelco-D, Pelco-P (auto detection)
Video output:	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / CVBS
Audio:	—
Number of presets:	256
Route settings:	10
Horizontal scan:	✓
Park action:	Call the set function (tour, scan, etc.) after specified dwell time
Alarm inputs / outputs:	—
Main features:	• Intelligent 3D Positioning System • 3D-DNR - Digital Noise Reduction • D-WDR - Wide Dynamic Range • EIS - Electronic Image Stabilization • IR illuminator optimization • BLC/HLC - Back Light / High Light Compensation • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Configurable Privacy Zones
OSD menu:	OSD menu available via Hikvision HD-TVI recorder
Vandal-proof:	—
"Index of Protection":	IP66
Power supply:	24 V AC
Power consumption:	≤ 40 W
Housing:	Speed Dome, Metal
Color:	White
Operation temp:	-30 °C ... 65 °C
Weight:	4.5 kg
Dimensions:	Ø 220 x 353 mm
Supported languages:	English, Polish
Manufacturer / Brand:	Hikvision
SAP Code:	301205024
Guarantee:	3 years