

Code: VI-1500/R1U

UPS **VI-1500/R1U** 1500 VA PowerWalker

The VI-1500/R1U UPS is a professional device used to maintain the operation of the components connected to it. The device is mounted to RACK 19" cabinet.



Nominal power:	900 W
Apparent Power:	1500 VA
Input voltage:	165 ... 290 V AC
Input frequency:	45 ... 55 Hz
Output voltage:	230 V AC (Pure Sine Wave)
Output frequency:	50 Hz
Voltage adjustment:	± 10 %
Frequency adjustment:	—
Transfer time:	max. 4 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	4 x 6V/9Ah
Estimated battery operation time:	• 3.1 minutes @ 100% load • 12.1 minutes @ 50% load
Number of outputs:	4 pcs IEC320 C13 socket
Management software:	PowerMaster
Protections:	• Glass Fuse • Overvoltage • Overload protection • EPO (Emergency power off) switch
Operation state indication:	• LCD display: operation mode, battery charging level, in/out voltage level • Sound signaling - with Mute function
Main features:	• Auto restart while AC is recovering • "Cold Start" function • Expansion slot • Battery charge and maintenance control • USB/RS-232 communication port



DATA SHEET

Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	RACK
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 % (non-condensing)
Weight:	16.31 kg
Dimensions:	435 x 400 x 44 mm ; RACK 19", 1U
Manufacturer / Brand:	PowerWalker
Guarantee:	2 years