


DATA SHEET

Code: TR-40VA/IT AC POWER SUPPLY ADAPTER **TR-40VA/IT** SATEL

410



The power adapter is intended to be used in installations, which according to the CE Directives require the use of safety isolating transformer. Transformer windings are isolated and sealed with polyurethane inside self-extinguishing housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work!

| Adapter type: | Transforming |
|-------------------------------|---|
| Power voltage: | 230 250 V AC |
| Frequency range: | 47 63 Hz |
| Output voltage: | 16 V, 18 V AC |
| Maximal load: | 2.22 A |
| EN norm: | EN61558-2-6 |
| Test voltage between PRI/SEC: | AC 4kV RMS |
| Safety class: | II |
| Isolation class: | B (130°C) |
| "Index of Protection": | IP44 |
| Output power: | 40 VA |
| Application: | to alarm systems powering to automatic systems to low-voltage light installation powering |



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

| Output: | 2 pcs |
|-----------------------|------------------|
| Weight: | 1.01 kg |
| Dimensions: | 124 x 72 x 67 mm |
| Manufacturer / Brand: | SATEL |
| Guarantee: | 2 years |

