

DATA SHEET

Code: DS-KH6320-WTE1-W

INDOOR PANEL Wi-Fi / IP **DS-KH6320-WTE1-W** Hikvision

The DS-KH6320-WTE1-W panel has been designed to create a simple and effective system of local communication.

A device dedicated to work with modular video doorphones Hikvision IP. It can be also used as simple alarm control panel, or notification module by the support 8 alarm inputs.

The device is dedicated to work with Hikvision IP video doorphones. In addition, the device has the ability to work with the **Hik-Connect** application on mobile devices.



Compatibility:	Hikvision IP Video Doorphones
Shield:	7 " - capacitive touch screen
Resolution:	1024 x 600
Internal memory:	128 MB (built-in)
Main features:	Wi-Fi module - IEEE 802.11 b/g/n, Microphone built-in, Speakers built-in, Bidirectional communication, Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, Automatically capture and save photos if there is no response to the bell button, IP Hikvision cameras support, The ability of direct communication between two or more panels, Register a short voice message if there is no response to the bell button Support for capturing a photo during video calls The microSD cards support max. 32 GB (not included) The device is fully configurable via the iVMS4200 software. In addition, the device has the ability to work with the Hik-Connect application on mobile devices
Controlling:	capacitive touch screen



DATA SHEET

Default administrator password:	The administrator password should be set at the first start
Default password for securing the zone:	-
Alarm inputs:	8
Alarm outputs:	2
Power supply:	• 12 V DC, • IEEE 802.3af
Power consumption:	≤ 6 W
Color:	White
Operation temp:	-10 °C 55 °C
Weight:	0.34 kg
Dimensions:	200 x 140 x 25 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305301796
Guarantee:	3 years