

DATA SHEET

Code: XVR5104HS-I2

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR XVR5104HS-I2 4 CHANNELS DAHUA

The XVR5104HS-I2 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



| Standard: | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP |
|-----------------------------|--|
| Video inputs: | 4 pcs BNC |
| Video outputs: | 1 pcs HDMI 1 pcs VGA |
| Audio inputs: | • 1 pcs - CINCH • 4 - Audio support via coaxial cable, HD-CVI only |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | AI Coding / H.265+ / H.265 / H.264+ / H.264 |
| Image records resolutions: | • AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1440 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 • IP : max. 6 Mpx - 3072 x 2048 |
| Recording speed adjustment: | 6 Mpx IP @ 1 25 fps 5M-N @ 1 10 fps 4M-N @ 1 15 fps 1080p @ 1 15 fps 1080N @ 1 25 fps 720p @ 1 25 fps 960H @ 1 25 fps for each channel |
| Operation modes: | 4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 2 x IP |
| Recording modes: | Manual, Motion Detection, Schedule |



DATA SHEET

| Supported hard drives: | 1 x 6 TB SATA |
|-------------------------------------|--|
| External storage devices backup: | Save single frames and whole records from DVR drive to the USB drive |
| Searching and playback the records: | Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) Intelligent face search AI - simultaneous search in the archive of face recordings based on max 8 photos taking into account the similarity threshold (for each photo separately) 1/4 channel synchronous playback |
| Network functions: | Full support via network, Remote records copying, Web Server built-in max. 128 on-line users |
| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Alarm inputs / outputs: | - |
| PTZ control: | IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P |
| Motion Detection: | Split the screen into zones : 22 x 18 motion zones |
| Main features: | Cooperation with Dahua devices working in the concept of the Internet of Things (IoT), POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window, SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle Coax Audio/Alarm support, Intelligent image analysis: crossing the line (tripwire), crossing the line (tripwire), abandoned/missing object, classification of people and vehicles advanced face recognition and search functions Support for up to 10 face databases, including 10 000 face images Detection of faces not included in the device database Searching for faces in recordings based on max 8 selected photos with the ability to independently set the similarity threshold for each photo |
| USB: | 2 pcs USB 2.0 |
| Mouse support: | ✓ |
| IR remote controller in the set: | - |
| Power supply: | 12 V DC / 1.5 A (power adapter included) |
| Color: | Black |
| Weight: | 0.84 kg |
| Dimensions: | 260 x 236 x 48 mm |
| Supported languages: | Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian |
| Country of origin: | China |
| Manufacturer / Brand: | DAHUA |



DATA SHEET

| Guarantee: | 3 years |
|------------|---------|