

Code: UT-275

CLAMP METER FOR EARTHING RESISTANCE AND LEAKAGE CURRENT **UT-275** UNI-T

The UT-275 clamp meter allows you to measure the earthing resistance and leakage current.



DC current measurement:	—
AC current measurement:	0 ... 99 mA $\pm$ (2.5% + 20 mA) @ 0.1 mA , 100 ... 299 mA (2.5% + 20 mA) @ 1 mA , 0.30 ... 2.99 A $\pm$ (2.5% + 0.1 A) @ 0.01 A , 3 ... 30 A $\pm$ (2.5% + 0.1 A) @ 0.1 A
Resistance measurement:	0.01 ... 0.099 Ω $\pm$ (2% + 0.02 Ω) @ 0.001 Ω , 0.1 ... 0.99 Ω $\pm$ (2% + 0.02 Ω) @ 0.01 Ω , 1.0 ... 49.9 Ω $\pm$ (1.5% + 1 Ω) @ 0.1 Ω , 50.0 ... 99.5 Ω $\pm$ (2% + 0.5 Ω) @ 0.5 Ω , 100 ... 199 Ω $\pm$ (3% + 1 Ω) @ 1 Ω , 200 ... 395 Ω $\pm$ (10% + 5 Ω) @ 5 Ω , 400 ... 590 Ω $\pm$ (20% + 10 Ω) @ 10 Ω , 600 ... 1000 Ω $\pm$ (25% + 20 Ω) @ 20 Ω
Automatic change of measuring ranges:	✓
RS-232:	—
USB:	—
Main features:	• Freezing the highest or lowest measurement, • Hold - stopping the meter reading, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case
Power supply:	4 x 1.5V, type AA/LR6/FR6 battery - included



DATA SHEET

Weight:	1.33 kg
Dimensions:	304 x 104 x 68 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

