

Code: VTO4202F-P-S2

## VIDEO DOORPHONE **VTO4202F-P-S2** DAHUA

The module is designed for installation in DAHUA VTM12x series housings.

**Attention!** When selecting 2-wire devices, check the compatibility list available at the bottom of the page in the "files" section.

It is a hybrid module - it can work in a 2-Wire installation or as a standard IP video doorphone.



|                            |                                                                                                                                                         |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sensor:                    | 2 Mpx CMOS                                                                                                                                              |
| Lens:                      | 1.9 mm                                                                                                                                                  |
| View angle:                | 160 °                                                                                                                                                   |
| proximity reader built-in: | —                                                                                                                                                       |
| Image compression method:  | H.265                                                                                                                                                   |
| LED illuminator:           | —                                                                                                                                                       |
| IR illuminator:            | ✓                                                                                                                                                       |
| Compatibility:             | DAHUA                                                                                                                                                   |
| RS-485:                    | ✓                                                                                                                                                       |
| Mobile phones support:     | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a> |

|                        |                                                                                                                                                                                                                                                                                                                                                     |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:         | <ul style="list-style-type: none"> <li>• Bidirectional communication,</li> <li>• Microphone built-in,</li> <li>• Speakers built-in</li> <li>• WDR - 120 dB - Wide Dynamic Range,</li> <li>• 3D-DNR - Digital Noise Reduction,</li> <li>• Power output : 12 V DC / 100 mA,</li> <li>• Tamper detection - removing from mounting surface ,</li> </ul> |
| Power supply:          | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 2-Wire IP interface</li> </ul>                                                                                                                                                                                                                                                   |
| Power consumption:     | ≤ 12 W                                                                                                                                                                                                                                                                                                                                              |
| Housing:               | Aluminum                                                                                                                                                                                                                                                                                                                                            |
| Color:                 | Silver                                                                                                                                                                                                                                                                                                                                              |
| "Index of Protection": | IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone                                                                                                                                                                                                                                                |
| IK rating:             | IK07                                                                                                                                                                                                                                                                                                                                                |
| Operation temp:        | -30 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                    |
| Weight:                | 0.28 kg                                                                                                                                                                                                                                                                                                                                             |
| Dimensions:            | 100 x 100 x 49.3 mm                                                                                                                                                                                                                                                                                                                                 |
| Supported languages:   | Polish, English                                                                                                                                                                                                                                                                                                                                     |
| Manufacturer / Brand:  | DAHUA                                                                                                                                                                                                                                                                                                                                               |
| Guarantee:             | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                      |