

Code: DS-KV8413-WME1(B)

## WIRELESS VIDEO DOORPHONE **DS-KV8413-WME1(B)** Wi-Fi / IP Hikvision

Wi-Fi / IP video doorphone is dedicated to work with II generation IP Hikvision internal panels.

Video Doorphone is mounted in a flush-mounted housing.



|                              |                                                                               |
|------------------------------|-------------------------------------------------------------------------------|
| Sensor:                      | 2 Mpx                                                                         |
| Resolution:                  | 1920 x 1080                                                                   |
| Camera view angle:           | 129 °                                                                         |
| IR illuminator:              | ✓                                                                             |
| LED illuminator:             | —                                                                             |
| PIR detector:                | —                                                                             |
| Doorbell button:             | 4 pcs                                                                         |
| proximity reader built-in:   | 13.56 MHz S50                                                                 |
| Wireless transmission range: | The range limited only by the availability of the Wi-Fi network               |
| Wi-Fi standard:              | IEEE 802.11b / IEEE 802.11g / IEEE 802.11n                                    |
| Network interface:           | <ul style="list-style-type: none"> <li>• Ethernet</li> <li>• Wi-Fi</li> </ul> |
| RS-485 interface:            | ✓                                                                             |
| Video output:                | —                                                                             |



# DATA SHEET

|                          |                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video format:            | H.264                                                                                                                                                                                                                                                                                                                                                                                   |
| Supported audio formats: | G.711                                                                                                                                                                                                                                                                                                                                                                                   |
| Alarm inputs:            | 4 pcs                                                                                                                                                                                                                                                                                                                                                                                   |
| Main features:           | <ul style="list-style-type: none"><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• DNR - Digital Noise Reduction</li><li>• BLC - Back Light Compensation</li><li>• Bidirectional communication,</li><li>• Full support via network : WiFi / LAN,</li><li>• Tamper detection - removing from mounting surface</li><li>• Video Doorphone is mounted in a flush-mounted housing</li></ul> |
| Power supply:            | <ul style="list-style-type: none"><li>• PoE (802.3af)</li><li>• 12 V DC / 830 mA (max)</li></ul>                                                                                                                                                                                                                                                                                        |
| Power consumption:       | < 10 W (operation)                                                                                                                                                                                                                                                                                                                                                                      |
| Housing:                 | Aluminum + Plastic, Protects against weather conditions                                                                                                                                                                                                                                                                                                                                 |
| Mount:                   | Flush-mounted                                                                                                                                                                                                                                                                                                                                                                           |
| Color:                   | Black + Gray                                                                                                                                                                                                                                                                                                                                                                            |
| "Index of Protection":   | IP65                                                                                                                                                                                                                                                                                                                                                                                    |
| Operation temp:          | -40 °C ... 53 °C                                                                                                                                                                                                                                                                                                                                                                        |
| Weight:                  | 0.35 kg                                                                                                                                                                                                                                                                                                                                                                                 |
| Dimensions:              | 174 x 91 x 30 mm                                                                                                                                                                                                                                                                                                                                                                        |
| Supported languages:     | Polish, English, Bulgarian, Croatian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian                                                                                                                                                                                                                 |
| Manufacturer / Brand:    | Hikvision                                                                                                                                                                                                                                                                                                                                                                               |
| SAP Code:                | 305302438                                                                                                                                                                                                                                                                                                                                                                               |
| Guarantee:               | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                          |