

Code: VTH5421E(W)-H

## INDOOR PANEL IP **VTH5421E(W)-H** Wi-Fi / IP DAHUA

The VTH5421E(W)-H panel has been designed to create a simple and effective system of local communication. It can be also used as simple alarm control panel, or notification module by the support 6 alarm inputs. The set includes a handset.



Compatibility:	Interphone installation - DAHUA IP
Shield:	7 " capacitive touch screen
Resolution:	1024 x 600
Internal memory:	—
Memory card slot:	Micro SD memory cards up to 32GB support (possible local recording)

Main features:	<ul style="list-style-type: none"> <li>• Wi-Fi Module - 2.4 GHz IEEE 802.11 b/g/n,</li> <li>• Protections : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS,</li> <li>• Microphone built-in,</li> <li>• Speaker built-in,</li> <li>• Handset,</li> <li>• Echo suppression and reduction / digital noise reduction,</li> <li>• Bidirectional communication,</li> <li>• Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume,</li> <li>• The ability to automatically take and save photos if you do not answer to the bell button,</li> <li>• The ability to record a short video message in the absence of a response to the bell button,</li> <li>• The ability of direct communication between two or more panels,</li> <li>• IP Dahua cameras support,</li> <li>• RS-485 interface,</li> <li>• Power output : 12 V DC / 100 mA,</li> <li>• DND mode,</li> <li>• SOS support,</li> <li>• ONVIF compliance ,</li> </ul>
Controlling:	capacitive touch screen
Alarm inputs:	6 ( 1 - as a bell )
Alarm outputs:	1
Power supply:	<ul style="list-style-type: none"> <li>• 12 V DC / 1 A,</li> <li>• PoE (802.3af)</li> </ul>
Power consumption:	<ul style="list-style-type: none"> <li>≤ 5 W (operation)</li> <li>≤ 2 W (standby)</li> </ul>
Operation temp:	-10 °C ... 55 °C
Color:	Black / White
Weight:	0.57 kg
Dimensions:	236 x 130 x 23 mm
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>

