

Code: VMT-100M

MONITOR VGA, VIDEO, HDMI, AUDIO, REMOTE CONTROLLER **VMT-100M** 9.7 " VILUX

Professional CCTV monitor - solid metal housing and additional layer for matrix protection. Due to its picture ratio 4:3, this monitor is perfect solution for monitoring applications, because there is a natural image ratio (image is not horizontally scaled up).

It has two types of mounting. As standalone or VESA 75 mounting. This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

The device is designed to continuous work in closed spaces.

Attention! No batteries inside remote controller (1x BAT-CR2032).



| | |
|----------------------|--|
| Screen size: | 9.7 " |
| Native resolution: | 1024 x 768 px |
| Aspect ratios: | 4 : 3 |
| Matrix type: | TFT-LCD color matrix, Glossy matrix |
| Matrix backlight: | In LED technology |
| Supported standards: | PAL/NTSC |
| Contrast: | 800 : 1 |
| Brightness: | 350 cd/m ² |
| Viewable angles: | <ul style="list-style-type: none"> • 178 ° - horizontal • 178 ° - vertical |
| Response time: | 12 ms |
| Speakers built-in: | ✓ |

| | |
|----------------------------|--|
| Signal connectors: | <ul style="list-style-type: none">• Composite Video (BNC) sockets: 1x in, 1x out• 1x VGA• 1x HDMI• Audio: 1x Jack (for VGA) |
| Main features: | <ul style="list-style-type: none">• 3D Comb Filter• 3D Noise Reduction• Auto Picture Adjustment |
| Housing type: | Metal |
| Monitor mounting standard: | VESA 75 |
| Power supply: | 12 V DC / 1 A (power adapter included) |
| Power consumption: | <ul style="list-style-type: none">• ≤ 10 W (operation)• ≤ 0.5 W (Standby mode) |
| Monitor control: | OSD - by IR remote controller or monitor control keys |
| Operation temp: | 0 °C ... 50 °C |
| Weight: | 1.37 kg |
| Dimensions: | 234 x 194 x 40 mm |
| Supported languages: | Polish, English, French, Spanish, German, Portuguese, Russian, Italian |
| Manufacturer / Brand: | VILUX |
| Guarantee: | 2 years |