

Code: ASI1202M-D

ACCESS CONTROLLER + RFID **ASI1202M-D** DAHUA

External, autonomous access controller with a built-in fingerprint reader and RFID reader.



Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	max. 1 ... 3 cm
Autonomous operation:	✓
Keyboard built-in:	—
Doorbell button:	—
Tamper output:	✓
RS-485 interface:	✓
Communication:	Wiegand
Power supply:	12 V DC
Maximal current consumption:	250 mA
Identification time:	< 1.5 s
Network interface:	RJ-45 - 10/100 Base-T
Default IP address:	192.168.1.108
Default admin user / password:	admin / -

Main features:	<ul style="list-style-type: none">• Memory of 3000 fingerprint patterns• Memory of 30000 RFID cards• Full support via network• Function of protection against multiple use of the same card for access (anti-passback)• Door contact and request button for exit inputs• Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value• Port USB• Blue backlight
Operation temp:	-30 °C ... 50 °C
Permissible relative humidity:	5 ... 95 % (non-condensing)
Housing:	Vandal-proof, IK10, Metal + Tempered glass
"Index of Protection":	IP65
Color:	Black + Silver
Weight:	0.71 kg
Dimensions:	159 x 55 x 35 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years