

Code: BCS-B-DK43312

AHD, HD-CVI, HD-TVI, PAL CAMERA **BCS-B-DK43312** - 5 Mpx 3.3 ... 12 mm BCS BASIC

Megapixel camera with 1/2.9" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



Standard:	AHD / HD-CVI / HD-TVI / CVBS
Sensor:	1/2.9 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ 20 fps - AHD / HD-TVI, • 2560 x 1440 - 4 Mpx @ 25 fps - HD-CVI • 960 x 576 @ 25 fps - PAL
Range of IR illumination:	40 m
IR illuminator power adjustment:	Automatic
Lens:	3.3 ... 12 mm, F1.2
View angle:	<ul style="list-style-type: none"> • 82 ° ... 28 ° (manufacturer data) • 90 ° ... 35 ° (our tests result)
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω, selectable by switch
Audio:	—
OSD menu:	✓

Main features:	<ul style="list-style-type: none">• D-WDR - Wide Dynamic Range• DNR - Digital Noise Reduction• BLC - Back Light Compensation• FLC - The technology eliminates the tiring eyes flickering image effect• Sharpness - sharper image outlines• AGC - Automatic Gain Control• White Balance - ATW/Manual• Day/night mode• ICR - Movable InfraRed filter• Mirror - Mirror image
Power supply:	12 V DC / 420 mA
Power consumption:	< 5 W
Housing:	Dome, Metal
Color:	Graphite
"Index of Protection":	IP66
Vandal-proof:	—
Operation temp:	-20 °C ... 60 °C
Weight:	0.57 kg
Dimensions:	Ø 119 x 98 mm
Supported languages:	English
Manufacturer / Brand:	BCS BASIC
Guarantee:	3 years